



Model:

□ CIM1135



CIM1135 ON CIB230

### Features and Benefits

- 30.25" (768 mm) wide space-saving design.
- Produces up to 425kg of ice per day.
- *Energy and Environment*
  - Exceeds new 2018 DOE (Department of Energy) regulations.
  - Up to 20% more energy efficient than other models.
  - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
  - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
  - Built in Agion® ensures unbeatable antimicrobial protection.
  - Smart LED light indicates machine status and when cleaning is required.
  - Simple, one-touch controls for sanitization and descaling.
  - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

CIM1135 CUBE ICE MAKER

### Ice Form

### Bin Chart *Kits for Combining Wider Bins with Smaller Models*

FULL CUBE DIMENSIONS	
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (mm)	10 x 22 x 22



CUBE

ICE STORAGE BINS								
	Model No. Capacity Width	B25 110 kg 762 mm	B40 156 kg 762 mm	B42 160 kg 559 mm	B55 232 kg 762 mm	CIB230 232 kg 770 mm	CIB400 400 kg 1,220 mm	B110 388 kg 1,219 mm
Kits	CIM1135	Kit Not Required		N/A	Kit Not Required		BT100	BPF-1

### Options & Accessories

### Ice Maker Warranty

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIM1135	CD20B	CD200B

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts

Note: All modular cube CIM units can be installed with the O<sub>3</sub>-Matic™ Ozone Delivery System.




# ELEVATION SERIES CUBE ICE MAKER CIM1135

CIM1135 CUBE ICE MAKER


## Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".



## Dual Exhaust for Installation Flexibility



## Operating Requirements

	MINIMUM	MAXIMUM
		<b>50Hz</b>
Ambient Temp. Range Air	10 °C	43 °C
Water Temp.	4.4 °C	
Water Pressure	1.4 BAR	5.5 BAR

## Dimensions

ALL MODELS	
W x D x H (mm)	768 x 616 x 683

## Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage litres per 45 kg of Ice 32°C air/21°C water		kWH Used per 45 kg of ice @ 32°C air/ 21°C water	Watts Used Per Hr. @ 32°C air/ 21°C water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Refrigeration Capacity per hour
		21°C air/ 10°C water (kg)	32°C air/ 21°C water (kg)	Potable	Condenser						
CIM1135A	Air	425	374	68	-	52	1791	220-240/50/1	13.5	20	5.657

\* Daily ice production based on half cube configuration.

Notes:  
 Number of Wires: CIM1135: 3 (including ground)  
 Approx. Shipping Weight kg: CIM1135A 105  
 Refrigerant Type: R404A